

Bright, Clear & Colorful Digital Panel Meters

Variety of Direct Sensor Input – 47L Series

- IP 66 front panel
- Separable terminal block
- 4, 4 1/2 or 6 digits LED
- 6 LED colors selectable
- DC/AC, temperature, potentiometer, strain gauge and pulse input
- DC output and alarm output optional



- 12 models
- LED
- 4 or 4 1/2 or 6 digits
- IP 66

Six LED Colors – 47L Series



External Interface Output – 47D Series

- IP 66 front panel
- Separable terminal block
- 5 1/2 digit LCD
- Bargraph and sub display
- DC output, alarm output, Modbus and BCD output optional



- 5 models
- LCD
- 5 1/2 digits
- IP 66

Large 0.8" High LED – 40 Series

- 0.8" (20.3 mm) high red LED
- 3 1/2 or 4 digits
- DC voltmeter/ammeter or process meter
- Direct temperature input also available
- Display hold function



- 3 models
- LED
- 3 1/2 or 4 digits

1/32 DIN Size – 43DV2

- 48 x 24 mm panel size
- Easy-to-wire tension clamp connection
- Process scaling



- LED
- 4 digits

Line Powered

1/32 DIN Size – 43AL1

- 48 x 24 mm panel size
- Powered from a 4-20 mA current loop
- No external power supply needed
- Easy-to-wire tension clamp connection
- Process scaling

Loop Powered



- LED
- 4 digits

Field Indicator – 6DV / 6DV-B

- Powered from a 4-20 mA current loop
- No external power supply needed
- Scaling & linearization selectable via the front control buttons
- IP 66/67 field enclosure, aluminium or stainless steel
- ATEX / FM approval



6DV

6DV-B

- LED
- 4 digits
- IP 66/67

