

ORDERING INFORMATION

MODEL : R7C-YV4

PLEASE FILL IN THIS SECTION



Model _____

Company _____

Name _____

P/O No. _____

M-SYSTEM USE ONLY



Job No. _____

Ser No. _____ to _____

Sales _____

Approved by (Sales office) _____

Issued by (Sales office) _____

Specify the items you want to change. Default setting will be used if not specified.
 DEFAULT shows values in case of nothing specified.

■ OUTPUT RANGE SETTING (APPLIES TO BOTH CHANNELS)

ITEM	SET VALUE	DEFAULT VALUE
OUTPUT RANGE *1	<input type="checkbox"/> -10 - +10 V DC	-10 – +10V DC
	<input type="checkbox"/> -5 - +5 V DC	
	<input type="checkbox"/> 0 - 10 V DC	
	<input type="checkbox"/> 0 - 5 V DC	
	<input type="checkbox"/> 1 - 5 V DC	
	<input type="checkbox"/> PC Configurator setting	

*1. When you want to set each channel independently, Select "PC Configuration setting," then specify each channel in "OUTPUT RANGE SETTING (INDEPENDENT RANGE PER CHANNEL)."

■ OUTPUT RANGE SETTING (INDEPENDENT RANGE PER CHANNEL)

CHANNEL	SET VALUE	DEFAULT VALUE
OUTPUT 0 *2	<input type="checkbox"/> -10 - +10 V DC	-10 – +10V DC
	<input type="checkbox"/> -5 - +5 V DC	
	<input type="checkbox"/> 0 - 10 V DC	
	<input type="checkbox"/> 0 - 5 V DC	
	<input type="checkbox"/> 1 - 5 V DC	
OUTPUT 1 *2	<input type="checkbox"/> -10 - +10 V DC	-10 – +10V DC
	<input type="checkbox"/> -5 - +5 V DC	
	<input type="checkbox"/> 0 - 10 V DC	
	<input type="checkbox"/> 0 - 5 V DC	
	<input type="checkbox"/> 1 - 5 V DC	
OUTPUT 2 *2	<input type="checkbox"/> -10 - +10 V DC	-10 – +10V DC
	<input type="checkbox"/> -5 - +5 V DC	
	<input type="checkbox"/> 0 - 10 V DC	
	<input type="checkbox"/> 0 - 5 V DC	
	<input type="checkbox"/> 1 - 5 V DC	
OUTPUT 3 *2	<input type="checkbox"/> -10 - +10 V DC	-10 – +10V DC
	<input type="checkbox"/> -5 - +5 V DC	
	<input type="checkbox"/> 0 - 10 V DC	
	<input type="checkbox"/> 0 - 5 V DC	
	<input type="checkbox"/> 1 - 5 V DC	

*2. Specify "0 – 10 V DC" for unused channel.

■ OUTPUT AT THE LOSE OF COMMUNICATION

ITEM	SET VALUE	DEFAULT VALUE
OUTPUT AT THE LOSE OF COMMUNICATION	<input type="checkbox"/> Hold the output (maintains the last data received normally)	Hold the output
	<input type="checkbox"/> Reset the output (to -15 % or approx. -11.5 V DC)	

■ BAUD RATE

ITEM	SET VALUE	DEFAULT VALUE
BAUD RATE	<input type="checkbox"/> 156 kbps	156 kbps
	<input type="checkbox"/> 625 kbps	
	<input type="checkbox"/> 2.5 Mbps	
	<input type="checkbox"/> 5 Mbps	
	<input type="checkbox"/> 10 Mbps	

■ STATION ADDRESS

AVAILABLE VALUE	SET VALUE	DEFAULT VALUE
1 to 64		0

■ SCALING

Set zero and full scale to each channel (zero scale to full scale)

CHANNEL	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE
OUTPUT 0	-32000 to +32000	to	0 to 10000
OUTPUT 1	-32000 to +32000	to	0 to 10000
OUTPUT 2	-32000 to +32000	to	0 to 10000
OUTPUT 3	-32000 to +32000	to	0 to 10000