

ORDERING INFORMATION

MODEL : R7C-DA16

PLEASE FILL IN THIS SECTION



Model
Company
Name
P/O No.

M-SYSTEM USE ONLY



Job No.	Approved by (Sales office)
Ser No.	Issued by (Sales office)
Sales	Approved by (Factory)
	Set by (Factory)

Specify the items you want to change. Default setting will be used if not specified.
 DEFAULT shows values in case of nothing specified.

■ TRANSFER RATE

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
TRANSFER RATE	<input type="checkbox"/> 156 kbps	156 kbps	<input type="checkbox"/>
	<input type="checkbox"/> 625 kbps		
	<input type="checkbox"/> 2.5 Mbps		
	<input type="checkbox"/> 5 Mbps		
	<input type="checkbox"/> 10 Mbps		

■ STATION ADDRESS

AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
1 to 64		0	<input type="checkbox"/>

■ EXTENSION

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
EXTENSION	<input type="checkbox"/> No extension	No extension	<input type="checkbox"/>
	<input type="checkbox"/> Discrete input, 8 points/ 16 points		
	<input type="checkbox"/> Discrete output, 8 points/ 16 points		

■ OUTPUT AT THE LOSE OF COMMUNICATION *

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
OUTPUT AT THE LOSE OF COMMUNICATION	<input type="checkbox"/> Hold the output (maintains the last data received normally)	Hold the output	<input type="checkbox"/>
	<input type="checkbox"/> Reset the output (turned off)		

* Only for Discrete output extension module.