

ORDERING INFORMATION

MODEL : R7E-MS4

PLEASE FILL IN THIS SECTION



Model
Company
Name
P/O No.

M-SYSTEM USE ONLY



Job No.	Approved by (Sales office)
Ser No.	Issued by (Sales office)
Sales	Approved by (Factory)
	Set by (Factory)
	Ser No.

Specify the items you want to change. Default setting will be used if not specified.

DEFAULT shows values in case of nothing specified.

■ ETHERNET PARAMETERS

ITEM	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
IP Address	0 to 255 (integer)		192.168.0.1	<input type="checkbox"/>
Subnet Mask			255.255.255.0	
Linger	0 to 32767 (integer) TCP Socket closed after no communication (Set 1800 for 180.0 sec.) for the preset time.		1800	
			1800	
			1800	
			1800	

■ EXTENSION

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
EXTENSION	<input type="checkbox"/> No extension	No extension	<input type="checkbox"/>
	<input type="checkbox"/> Discrete input, 8 points / 16 points		
	<input type="checkbox"/> Discrete output, 8 points / 16 points		

■ OUTPUT AT THE LOSE OF COMMUNICATION *

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
OUTPUT AT THE LOSE OF COMMUNICATION	<input type="checkbox"/> Hold the output (maintains the last data received normally)	Hold the output	<input type="checkbox"/>
	<input type="checkbox"/> Reset the output (turned off)		

* Only for Discrete output extension module.

■ **SCALING**

Set zero and full scale to each channel (zero scale to full scale)

CHANNEL	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 0	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>
INPUT 1	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>
INPUT 2	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>
INPUT 3	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>

■ **CONVERSION RATE**

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
CONVERSION RATE / CONVERSION ACCURACY	<input type="checkbox"/> 80ms / ±0.1%	80ms / ±0.1%	<input type="checkbox"/>
	<input type="checkbox"/> 40ms / ±0.2%		
	<input type="checkbox"/> 20ms / ±0.4%		
	<input type="checkbox"/> 10ms / ±0.8%		