

ORDERING INFORMATION

MODEL : R30SV4

PLEASE FILL IN THIS SECTION



Model
Company
Name
P/O No.

M-SYSTEM USE ONLY



Job No.	Approved by (Sales office)
Ser No.	Issued by (Sales office)
Sales	Approved by (Factory)
	Set by (Factory)

Specify the items you want to change. Default setting will be used if not specified.
 DEFAULT shows values in case of nothing specified.

■ INPUT RANGE SETTING

CHANNEL	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 1	<input type="checkbox"/> -10 to +10 V DC <input type="checkbox"/> -5 to +5 V DC <input type="checkbox"/> -1 to +1 V DC <input type="checkbox"/> 0 to 10 V DC <input type="checkbox"/> 0 to 5 V DC <input type="checkbox"/> 1 to 5 V DC <input type="checkbox"/> 0 to 1 V DC <input type="checkbox"/> -0.5 to +0.5 V DC <input type="checkbox"/> -20 to +20 mA DC <input type="checkbox"/> 4 to 20 mA DC <input type="checkbox"/> 0 to 20 mA DC <input type="checkbox"/> CH Disable	-10 to +10 V DC	<input type="checkbox"/>
INPUT 2	<input type="checkbox"/> -10 to +10 V DC <input type="checkbox"/> -5 to +5 V DC <input type="checkbox"/> -1 to +1 V DC <input type="checkbox"/> 0 to 10 V DC <input type="checkbox"/> 0 to 5 V DC <input type="checkbox"/> 1 to 5 V DC <input type="checkbox"/> 0 to 1 V DC <input type="checkbox"/> -0.5 to +0.5 V DC <input type="checkbox"/> -20 to +20 mA DC <input type="checkbox"/> 4 to 20 mA DC <input type="checkbox"/> 0 to 20 mA DC <input type="checkbox"/> CH Disable	-10 to +10 V DC	<input type="checkbox"/>

CHANNEL	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 3	<input type="checkbox"/> -10 to +10 V DC <input type="checkbox"/> -5 to +5 V DC <input type="checkbox"/> -1 to +1 V DC <input type="checkbox"/> 0 to 10 V DC <input type="checkbox"/> 0 to 5 V DC <input type="checkbox"/> 1 to 5 V DC <input type="checkbox"/> 0 to 1 V DC <input type="checkbox"/> -0.5 to +0.5 V DC <input type="checkbox"/> -20 to +20 mA DC <input type="checkbox"/> 4 to 20 mA DC <input type="checkbox"/> 0 to 20 mA DC <input type="checkbox"/> CH Disable	-10 to +10 V DC	<input type="checkbox"/>
INPUT 4	<input type="checkbox"/> -10 to +10 V DC <input type="checkbox"/> -5 to +5 V DC <input type="checkbox"/> -1 to +1 V DC <input type="checkbox"/> 0 to 10 V DC <input type="checkbox"/> 0 to 5 V DC <input type="checkbox"/> 1 to 5 V DC <input type="checkbox"/> 0 to 1 V DC <input type="checkbox"/> -0.5 to +0.5 V DC <input type="checkbox"/> -20 to +20 mA DC <input type="checkbox"/> 4 to 20 mA DC <input type="checkbox"/> 0 to 20 mA DC <input type="checkbox"/> CH Disable	-10 to +10 V DC	<input type="checkbox"/>

Default value for CH Disable.

■ DATA RANGE

Set zero and full scale to each channel (zero scale to full scale)

CHANNEL	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 1	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>
INPUT 2	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>
INPUT 3	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>
INPUT 4	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>

■ CONVERSION RATE

CHANNEL	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 1 to 4 CONVERSION RATE / CONVERSION ACCURACY	<input type="checkbox"/> 80 ms / ±0.1% <input type="checkbox"/> 40 ms / ±0.2% <input type="checkbox"/> 20 ms / ±0.4% <input type="checkbox"/> 10 ms / ±0.8%	80ms / ±0.1%	<input type="checkbox"/>